What is claimed is:

- 1. A substrate providing an optical waveguide and having steps for positioning formed on at least one side thereof.
- 2. A substrate according to claim 1 wherein an optical element is mounted on and connected to said optical waveguide.
- 3. A substrate according to claim 1 wherein inclined grooves that incline relative to the propagation direction of the light are formed on said optical waveguide, and a light reflecting device that reflects light propagated along said optical waveguide to the outside of said optical waveguide is provided on said inclined grooves.
- 4. A substrate according to claim 1 wherein inclined grooves that incline relative to the propagation direction of the light are formed on said optical waveguide, and an optical wavelength selecting device that selects the light having a wavelength in a desired range from the light propagated through said optical waveguide and extracts it to the outside of said optical waveguide is provided on said inclined groove.
- 5. A substrate having optical elements mounted thereon, and steps for positioning formed on at least one side thereof.

5

Blut

- 6. An optical fiber connecting end member having formed therein a hole for accommodating and fixing one end of said substrate and optically connecting the substrate to the optical fiber, wherein steps for positioning said substrate are formed on the substrate in said hole.
- 7. An optical element housing member having formed therein a hole for accommodating and fixing one or the other end of said substrate and optically connecting the substrate to an optical element, wherein steps for positioning said substrate are formed in said hole.

ID ID ISUBAL

5

8. An optical module that provides the substrate according to claims 1 and the optical fiber connecting end member according to the claim 6 and/or the optical element housing member according to claim 7.

5017

- 9. An optical module according to claim 8 wherein two of said optical fiber connecting end members are disposed opposite to each other so as to sandwich said optical element housing member, and said substrate on which said optical fiber connecting end member is accommodated and fixed is optically connected to the optical element of said optical element housing member.
- 10. An optical module according to claims 8 wherein said substrate is pressed against the optical fiber connecting end member by the elastic force of an elastic member.

Out (out

11. A fabrication method for the substrate according to claims 1 wherein steps for positioning are formed on at least one side of said substrate by anisotropic etching.

Add A2

DOESTOCE CETODA